

Friendship Cards

#PK50022 4 DESIGNS

MATERIALS



Isacord Thread Colors

0111 Whale 2910 Grape 2320 Raspberry 4220 Island

2320 Raspberry 4220 Island Green 2532 Pretty in Pink 4410 Aqua Velva

2732 Frosted Orchid 4610 Deep Aqua

Note: One spool of 1000 meter thread is adequate for the project unless otherwise noted.

MATERIALS



Stabilizers

- OESD StabilStick TearAway (variation 1)
- OESD Medium Weight TearAway (variation 2)
- OESD Fuse and Seal CutAway

Fabrics/Textiles

• Start Here Embroidery Blanks by OESD - Greeting Card size A7 (5" x 7") folded.

Notion & Tools

- OESD Expert Embroidery Tape TearAway
- OESD Grippy Grid
- OESD Perfect Embroidery Press Cloth
- Embroidery Needle Sharp Size 75/11

Isacord Thread Colors

Per thread chart



GENERAL INSTRUCTIONS

The card instructions included in the collection are **general**. A sample card design that best demonstrates the technique is shown for demonstration purposes. Thread requirements will vary by design.

Note: Some thread colors in instructions have been changed or digitally enhanced for better visibility.

Step 1

- · Hoop one layer of StabilStick TearAway paper (shiny) side up.
- Use a pin or needle to score the paper.
- Remove the paper to reveal the adhesive surface.



Step 2

- · Load selected design into the machine.
- Design in the example is PK10001-02L.
- Thread the machine per the thread chart.
- Stitch Machine Step 1, Card Placement Guide.





Step 3

 Place the front of the card face up within the Card Placement Guide, lining up all edges.



Step 4

Stitch the remaining steps per the thread chart.



Step 5

- · Remove the hoop from the machine.
- · Remove the card and stabilizer from the hoop.
- On a flat surface, fold the stabilizer back and carefully cut the stabilizer away, close to the stitching.

Note: Cutting away the excess TearAway stabilizer prevents bending or creasing the cardstock.





Step 6

- Cut coordinating cardstock (or scrapbook paper) slightly smaller than the front of the card.
- Cut a piece of Fuse and Seal to fit. Following the package instructions, iron the Fuse and Seal to the wrong side of the cardstock (scrapbook paper).
- Let cool completely.



Step 7

- Place the card, front side down, onto a Perfect Embroidery Press Cloth.
- Remove paper from Fuse and Seal.
- Place the cardstock (scrapbook paper), right side up, onto the wrong side of the stitching.
- Iron to fuse to the card.
- · Let cool completely.



Step 8

• The card is complete. Enjoy!





Step 1

- 2 cards folded to 5" x 7".
- · Cut one card in half on the fold.





Step 2

- Hoop 1 layer of OESD Medium Weight TearAway stabilizer.
- · Load selected design into the machine.
- Design in the example is PK10001-03L.
- Thread the machine per the thread chart.
- Stitch Machine Step 1, Card Placement Guide.



Step 3

- Place 5" x 7" piece of cardstock within the Card Placement Guide, lining up all edges.
- Tape in place to secure.
- Note: Expert Embroidery Tape TearAway will not leave residue on the paper or tear the cardstock.





Step 4

• Stitch the remaining steps per the thread chart.



Step 5

- Remove the hoop from the machine.
- Remove the card and stabilizer from the hoop.
- On a flat surface, fold the stabilizer back and carefully cut the stabilizer away, close to the stitching.

Note: Cutting away the excess TearAway stabilizer prevents bending or creasing the cardstock.





Step 6

 Cut I piece of Fuse and Seal slightly smaller than the size of your card.






Step 7

- Following the package instructions, iron the Fuse and Seal to the wrong side of the embroidered card.
- Let cool completely.



Step 8

· Once cool, remove the paper backing.



Step 9

- Place the embroidered card over the front of the second card.
- Iron to fuse to the card.
- Let cool completely.







Step 10

• The card is complete. Enjoy!

